

CONTACT CLEAN™

DESCRIPTION

Contact Clean™ is a non-flammable cleaner for removing grease, oil, and contaminants from sensitive electronics and electrical equipment to prevent contact failure.

- Nonflammable and nonconductive
- Effectively cuts through and removes grease, oil, and dirt
- Fast-evaporating formula dries residue-free in seconds
- Strong aerosol jet
- NSF category K2, registration #154540.
- VOC compliant (per Carb 310)

APPLICATIONS

- Removing contaminants from electrical parts
- Safely cleans most plastics and rubber compounds
- Instrument and equipment junction cleaning (PLCS, printed circuit boards, vehicle fuse boxes).

Directions for Use: Shake well before use. Spray on soiled surfaces.

TECHNICAL DATA

Physical state: Aerosol

Appearance: Clear liquid, ether-like odour

Density: 1.41g/ml (20°C /68°F)

VOC: 23.20 % (w/w) (CARB 310)

Kauri-Butanol Value (KB), ASTM D 1133-61: 20.0

Surface Tension, ASTM D 1331: 15.99 mN/m (dynes /cm)

Flash Point: This material is classified as non-flammable per UNECE classification procedures

Engineering controls: Provide adequate ventilation

Incompatible substances: Oxidizing agents

Storage: Keep container tightly closed, store below 50°C/122°F

Shelf life: Two (2) years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No. (M)	SDS
Aerosol	12 oz	53-C 712	L-165

(M) SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.